


版本 Rev.	日期 Date	变更文件号 ECN NO.	变更内容 Revisions	设计 By
V1.0	17.04.24		初版	王洪松

Dimension: (Unit: mm)




Common Rating

Step angle	1.8°
Position accuracy	1.8±0.9°
Dielectric strength	500VAC 1min
Insulation resistance	100MΩ(500VDC)
Insulation class	B
Temp rise(Max)	80K
Radial play	Max.0.02mm(Load 450g)
Axial play	Max.0.08mm(Load 900g)

Specification:

Current/phase	4.0 A
Voltage	3.2 V
DC Resistance/phase ±10%	0.8 Ω
Inductance/phase ±20%	3.2 mH
Holding torque	2.6 N·M
Detent torque	0.068 N·M
Inertia	0.52 kg·cm ²
Weight	1.4 kg

Motor Connctions:



设计 Designed	王洪松	日期 Date	2017.04.24	材料 Material	深圳市雷赛智能控制股份有限公司 SHENZHEN LEADSHINE TECHNOLOGY CO., LTD.
审核 Checked	刘佩峰	2017.04.24		第一角画法 First Angle projection	名称 Title
批准 Approved	田天胜	2017.04.24		重量 Weight 比例 Scale 阶段标记 Stage Mark	混合式步进电机
料号 Part No.				共 1 页 第 1 页 Sheet 1 of 1	57CM26-4A-0-16
					图号 DWG. NO.